

財團法人全國認證基金會 Taiwan Accreditation Foundation Certificate of Accreditation

(Certificate No: L2947-240522)

This is to certify that

Wistron NeWeb Corporation Reliability Test Lab.

20 Park Avenue II, Hsinchu Science Park, Hsinchu, Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria: ISO/IEC 17025:2017; CNS 17025:2018

Accreditation Number : 2947

Originally Accredited: February 16, 2015

Effective Period: May 22, 2024 to May 21, 2027

Accredited Scope: Testing Field, see described in the Appendix

Scan to verify

Yi-Ling Chen

Yi-Ling Chen President, Taiwan Accreditation Foundation May 22, 2024

Certificate No: L2947-240522

Accreditation Number: 2947

Laboratory Head: TSAI, Duke

19. 99 Electronic and Electric Electrical & Electronic Products E002 Electrostatic discharge immunity test IEC 61000-4-2

Contact Discharge: ±8 kV Air Discharge: ±15 kV

Approval Signatory: CHANG, Tomson; TSAI, Duke

E003

- 1. Low Temperature test
- 2. High temperature test
- 3. Change of temperature
- 4. Damp heat, steady state
- 1. IEC 60068-2-1;
- 2. IEC 60068-2-2;
- 3. IEC 60068-2-14, Test Na/Nb;
- 4. IEC 60068-2-78;
- 1. (-50 to 0) °C;
- $2. \leq 125 \, ^{\circ}\text{C}$
- 3. (-50 to 125) °C, Max. 5 °C/min;
- 4. (30 to 40 °C), (85 to 93) %RH;

Approval Signatory: CHANG, Tomson; TSAI, Duke

E003 Salt Spray test IEC 60068-2-11

Approval Signatory: CHANG, Tomson; TSAI, Duke

E003 Drop test

IEC 60068-2-31 (free fall) Drop length: 50 cm & 100 cm

Approval Signatory: CHANG, Tomson; TSAI, Duke

E003 Vibration test IEC 60068-2-6

TEC (00008-2-0

IEC 60068-2-64: 2008 Frequency: (5 to 2000) Hz

Acceleration: (0 to 10) GDisplacement: $\leq 1 \text{ mm}$

Waveform: Sine wave, Random wave

Approval Signatory: CHANG, Tomson; TSAI, Duke

P2, total 3 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix



Certificate No: L2947-240522

E003 Degrees of Protection against Water Indicated IEC 60529 IPX7

Approval Signatory: CHANG, Tomson; TSAI, Duke

(Null below)







